


0.6/1 kV PVC İZOLELİ, ÇOK DAMARLI BAKIR İLETKENLİ KABLOLAR

0.6/1 kV PVC INSULATED, MULTI CORE CABLES WITH COPPER CONDUCTOR



KOD / CODE

YVV-U, YVV-R, CU/PVC/PVC, NYY

U: Som İletken

R: Örgülü Rijit İletken

YVV-U, YVV-R, CU/PVC/PVC, NYY

U: Solid Conductor

R: Stranded Conductor

STANDARTLAR

TS IEC 60502, VDE 0276

STANDARTS

TS IEC 60502, VDE 0276

KULLANIM ALANLARI / APPLICATION

GÜÇ MERKEZLERİNDE, ŞALT ve ENDÜSTRİ TESİSLERİNDE, YEREL ENERJİ DAĞITIMINDA GÜÇ KABLOSU OLARAK MEKANİK HASAR RİSKİNİN OLMADIĞI YERLERDE HARIÇTE, DAHİLDE, TOPRAK ALTINDA veya KABLO KANALLARINDA KULLANILIR.

INDOORS and OUTDOORS, IN CABLE DUCKS, UNDERGROUND, IN POWER OR SWITCHING STATIONS, LOCAL ENERGY DISTRIBUTIONS, INDUSTRY PLANTS, WHERE THERE IS NO RISK OF MECHANICAL DAMAGE.

TEKNİK ÖZELLİKLER / TECHNICAL CHARACTERISTIC

ÇALIŞMA SICAKLIĞI (MAKS.) 70°C

OPERATING TEMPERATURE (MAX.) 70°C

KISA DEVRE SICAKLIĞI (MAKS.) 160°C (max. 5 sn.)

OPERATING TEMPERATURE 160°C (max. 5 sec.)

KESİT ≤ 300mm 160°C (max. 5 sn.)

CROSS SECTION ≤ 300mm 160°C (max. 5 sec.)

KESİT > 300mm 140°C (max. 5 sn.)

CROSS SECTION > 300mm 140°C (max. 5 sec.)

ANMA GERİLİMİ 0.6/1 kV

RATED VOLTAGE 0.6/1 kV

BÜKÜLME YARIÇAP (min.) 12xDIŞ ÇAP

BENDING RADIUS (min.) 12xOUTER DIAMETER

YAPISI / CONSTRUCTION

BİR VEYA ÇOK TELLİ BAKIR İLETKEN

SOLID OR STRANDED COPPER CONDUCTOR

PVC İZOLE

PVC INSULATION

PVC DOLGU

PVC FILLER

PVC DIŞ KILIF

PVC OUTER SHEAT

KOD NO CODE NR	BOYUT VE AĞIRLIKLAR (DIMENSIONS AND WEIGHTS)				ELEKTRİKSEL ÖZELLİKLER (ELECTRICAL PROPERTIES)		
	NOMİNAL KESİT NOMINAL CROSS-SECTION	DIŞ ÇAP (yaklaşık) OVERAL DIAMETER (approx.)	NET AĞIRLIK (yaklaşık) NET WEIGHT (approx.)	SEVK UZUNLUĞU DELIVERY LENGHT	İLETKEN DC DİRENCİ 20°C'de max. DC Conductor Resistance at 20°C	AKIM TAŞIMA KAPASİTESİ CURRENT CARRYING CAPACITY	
						mm ²	mm
940 470	3x16+10	21.5	970	1000	1.1500	98	80
940 471	3x25+16	25.0	1400	1000	0.7270	128	106
940 472	3x35+16	27.0	1750	1000	0.5240	157	131
940 473	3x50+25	31.0	2400	1000	0.3870	185	159
940 474	3x70+35	35.0	3300	1000	0.2680	228	202
940 475	3x95+50	40.0	4400	1000	0.1930	275	244
940 476	3x120+70	44.5	5550	500	0.1530	313	282
940 477	3x150+70	48.0	6550	500	0.1240	353	324
940 478	3x185+95	53.0	8200	500	0.1991	399	371
940 479	3x240+120	60.5	10600	500	0.0754	464	436
940 480	3x300+150	68.0	13100	250	0.0601	524	481
940 481	3x400+185	76.0	17000	250	0.0470	600	560