

# PVC İZOLELİ, ÇOK DAMARLI BÜKÜLGEN BAKIR İLETKENLİ KABLOLAR

PVC INSULATED, MULTICORE CABLES WITH FLEXIBLE COPPER CONDUCTOR



## KOD / CODE

H03VH-H, H05VH, CU/PVC (KORDON)

İnce Çok Tellli İletken

H03VH-H, H05VH, CU/PVC

Fine-Stranded Conductor

## STANDARTLAR

TS 9760, VDE 0281, IEC 227-42, HD 21.5 S3  
TS 9760, VDE 0281, IEC 227-42, HD 21.5 S3

## KULLANIM ALANLARI / APPLICATION

AZ MEKANİK ZORLAMALARIN BULUNDUĞU KAPALI VE KURU YERLERDE, EV ALETLERİNDE, BUHARLI VE RUTUBETLİ YERLERDE KULLANILIR.

FOR HOUSEHOLD APPLIANCES (REFRIGATORS, SPIN DRYERS, ETC.) UNDER MEDIUM MECHANICAL STRESSES, ALSO IN DAMP AND WET SPACES.

## TEKNİK ÖZELLİKLER / TECHNICAL CHARACTERISTIC

ÇALIŞMA SICAKLIĞI (MAKS.) 70°C  
OPERATING TEMPERATURE (MAX.) 70°C

KISA DEVRE SICAKLIĞI (MAKS.) 160°C (max. 5 sn.)  
OPERATING TEMPERATURE 160°C (max. 5 sec.)

ANMA GERİLİMİ 300/500 V, 300/500 V  
RATED VOLTAGE 300/500 V, 300/500 V

## YAPISI / CONSTRUCTION

İNCE ÇOK TELLİ BAKIR İLETKEN  
FINE-STRANDED COPPER CONDUCTOR  
PVC İZOLE  
PVC INSULATION

BOYUT VE AĞIRLIKLAR (DIMENSIONS AND WEIGHTS)					ELEKTRİKSEL ÖZELLİKLER (ELECTRICAL PROPERTIES)	
KOD NO CODE NR	NOMİNAL KESİT NOMINAL CROSS-SECTION	DIŞ ÇAP (yaklaşık) OVERAL DIAMETER (approx.)	NET AĞIRLIK (yaklaşık) NET WEIGHT (approx.)	SEVK UZUNLUĞU DELIVERY LENGHT	İLETKEN DC DİRENCİ 20°C'de max. DC Conductor Resistance at 20°C	AKIM TAŞIMA KAPASİTESİ CURRENT CARRYING CAPACITY
	mm <sup>2</sup>	mm	kg/km	m	(ohm/km)	A
930 028	2x0.50*	2.40x4.80	21	100	39.0	8
930 029	2x0.75	2.60x5.20	26	100	26.0	13
930 030	2x1.0	2.80x5.60	32	100	19.5	16
930 031	2x1.5	3.10x6.20	43	100	13.3	20
930 032	2x2.5	3.40x6.80	62	100	7.98	27
930 033	2x4.0	4.20x8.40	97	100	4.95	34

\*300/300V H03VV-F



## CAMPER TELİ / JUMPER WIRE

İLETKEN\* 0.6 mm ÇAPINDA SOM ELEKTROLİTİK (TAVLI) BAKIR.  
CONDUCTOR\* SOLID ANNEALED COPPER AT THE DIAMETER OF 0.6 mm

YALITKAN MAVİ veya BEYAZ RENKTE POLİVİNİKLORÜR (PVC)  
(ASTM D 1248)  
INSULATION POLYVINCHLORIDE (PVC) HAVING THE COLOURS OF BLUE AND WHITE (ASTM D 1248)

ÇEKİRDEK OLUŞUMU MAVİ veya BEYAZ RENKLİ İZOLELER BİR İKİLİ (PER) OLUŞTURACAK ŞEKİLDE BİRLİKTE BÜKÜLÜR.

CABLE ASSEMBLY BLUE and WHITE COLOURED INSULATIONS ARE TWISTED TOGETHER TO FORM A PAIR.

## TEKNİK ÖZELLİKLER / TECHNICAL CHARACTERISTIC

İLETKEN DİRENCİ 66 Ωkm  
CONDUCTOR RESISTANCE

YALITIM DİRENCİ 200 MΩ km  
INSULATION RESISTANCE 1000V DC

## KULLANIM ALANLARI / APPLICATION

REPERTÖR VE SAHA DOLAPLARINDA KULLANILIR.  
DESIGNED TO USE AS CONNECTION CABLE.

İLETKEN ÇAPI CONDUCTOR DIAMETER	PER SAYISI NUMBER OF PAIRS	NET AĞIRLIK (KG/KM) NET WEIGHT	SEVK UZUNLUĞU DELIVERY LENGHT	KABLO DIŞ ÇAPI OVERALL DIAMETER	STANDART UZUNLUK TOLERANSI LENGHT TOLORANCE
mm		kg	m	mm	%
0.6	1	7.5	500	2	5