

DAHİLİ TESİSAT TELEFON KABLOSU (PDV-K)

INDOOR TYPE TELEPHONE CABLES

ALKAN KABLO PDV-K



KABLO YAPISI / CONSTRUCTION

İLETKEN CONDUCTOR	IEC-228; DIN VDE 0295; HD 393 SINIF 1 ELEKTROLİTİK MONO BAKIR IEC-228; DIN VDE 0295; HD 393 CLASS 1 ELECTROLYTIC SOLID COPPER
YALITKAN INSULATION	SOLID PE KOMPAUND SOLID PE COMPOUND
YALITIM RENK COLOUR CODE	TS 3930 TS 3930
BÜKÜM STRANDING	BKZ. PDV/PDV-K KABLOLARI YAPISI LOOT AT PDV/PDV-K CABLES CONSTRUCTION
AYIRICI BANT WRAPPING	PES BANT (10 ÇİFT ÜSTÜ) PES TAPE (ABOVE 10 PAIR)
DIŞKILIF SHEATH	PVC KOMPAUND PVC COMPOUND
DIŞKILIF RENGİ SHEATH COLOUR	RAL 7032 GRİ RAL 7032 GREY

ALEV GECİKTİRİCİ ÖZELLİK FLAME RETARDANT CHARACTERISTIC
İNCELTİLMİŞ DIŞ ÇAP SMALL OUTER DIAMETER
DÜŞÜK BÜKÜLME ÇAPI SMALL BENDING RADIUS

Not: PDV = Elektrolitik bakır iletken
PDV-K = Kalaylı bakır iletken
ESAS ALINAN STANDARTLAR: VDE 0816/TS 3930
Note: PDV = Electrolytic copper conductor
PDV-K = Tinned copper conductor
BASED ON VDE 0816/TS 3930 STANDARTS

TEKNİK ÖZELLİKLER / TECHNICAL CHARACTERISTIC

DC İLETKEN DİRENCİ CONDUCTOR RESISTANCE (MAX)	0.50 mm = 97.8 Ω km
YALITIM DİRENCİ INSULATION RESISTANCE (MIN)	5000 MΩ km
EFEKTİF KAPASİTE MUTUAL CAPACITY (MAX)	56 nF/km
ÇALIŞMATICAKLIĞI TEMPERATURE RANGE	-30°C ~ +70°C
TEST VOLTAJI (50 Hz) TEST VOLTAGE	1000 V
ÇALIŞMA VOLTAJI OPERATING VOLTAGE	300 V
BÜKÜLME ÇAPI BENDING RADIUS	8xKablo Ø
ALEV TESTİ FLAME TEST	IEC 332-1; VDE 0472 PART 804 EN 50265-2-1

KULLANIM ALANLARI / APPLICATION

BİNA İÇİ TESİSATLARDA SANTRAL VE ABONE DAĞITIMLARINDA KULLANILIRLAR
FOR INDOOR INSTALLATIONS, TELEPHONE EXCHANGE AND SUBSCRIBER DISTRIBUTIONS

KOD NO CODE NR		ÇİFTSAYISI VE İLETKEN ÇAPI NUMBER OF PAIRS AND WIRE DIAMETER (mm)	KABLO ÇAPI OVERAL DIAM ~(mm)	BAKIR AĞIRLIĞI COPPER WEIGHT ~(kg/km)	KABLO AĞIRLIĞI CABLE WEIGHT ~(kg/km)	STANDART UZUNLUK STANDART LENGHT (mt)
PDV	PDV-K					
830 43001	830 43001	1x2x0.50 mm	3.4	5.5	12	100/500/1000
830 43002	830 43002	2x2x0.50 mm	4.0	9.5	20	100/500/1000
830 43003	830 43003	3x2x0.50 mm	4.2	13	25	100/500/1000
830 43004	830 43004	4x2x0.50 mm	4.8	1.7	31	100/500/1000
830 43005	830 43005	6x2x0.50 mm	5.6	20	38	100/500/1000
830 43006	830 43006	8x2x0.50 mm	6.0	24	43	100/500/1000
830 43007	830 43007	10x2x0.50 mm	7.3	39	75	100/500/1000

ALKAN KABLO PDV-K